



Certificate Number

Manufacturer:

Fluke

Asset No:

XDEVS001

Model No:

SL935

Description:

Standard Resistor - Multiple

Serial No:

001

Procedure Used:

PICP-10194

Calibration Date:

5/31/2018

Process Instruments, Inc. certifies that the above instrument has been calibrated using standards traceable through the National Institute of Standards and Technology (NIST) or other national metrology institutes, or to accepted values of natural physical constants, or derived by the ratio type of self-calibration techniques, to the SI.

The reported uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. The reported uncertainty is valid only at the time of test and does not take into account any effects such as long-term drift, transportation or other factors that may affect the stability of this device.

This certificate and any included reports shall not be reproduced, except in full, without written permission from Process Instruments, Inc.

STANDARDS USED				
ID	Description	Due Date		
140078	Hart Scientific 2564 Thermistor Scanner Module	2/28/2019		
140124	Leeds & Northrup 4210 Standard Resistor - 1 Ohm	9/30/2018		
140132	Measurements International 6010B Current Comparator Resistance Bridge	7/31/2018		
140157	GE Thermometrics S25 Standard Thermistor	1/31/2019		

Notes:

Laboratory Environment:

Temperature:

22.84 °C

Humidity:

51.5 %RH

Approved By:

Karl W. Klevens

Quality Manager

P.O. Number:

Page 1/2

(412) 431-4600

FAX (412) 431-3792

www.procinst.com

This standard resistor was calibrated by comparing it to a standard resistor while in an air bath at 23.00° C ($\pm 0.05^{\circ}$ C) with an automatic current comparator resistance bridge. The value reported is the mean of the last 25 measurements of a run of at least 30 measurements taken. All values expressed are in terms of the SI 1990 values of voltage and/or resistance and in terms of the ITS-90.

Measured Va	alue	Uncertainty
1.00005942 Ω	@ 100.00 mADC	0.17 ppm
9999.9755 Ω	@ 0.30 mADC	0.33 ppm

End of Measurement Results