

Keysight Technologies

33330B/8472B Coaxial Detectors

DC to 18 GHz



Technical Overview

The Keysight Technologies, Inc. 33330B/8472B broadband coaxial detectors are widely used in applications such as the detecting element in leveling loops, power monitoring, and as wideband video detectors.

These detectors use a Low-Barrier Schottky Diode (LBSD), specially fabricated with low origin resistance and low junction capacitance. This results in improved broadband flatness and SWR over point-contact diode detectors, thus yielding more accurate measurements. These detectors also offer very good ruggedness and burnout protection. As with all Keysight detectors, these models integrate the diode with the other circuit elements thus minimizing stray reactance's and optimizing broadband performance.

In addition to superior RF characteristics, the LBS detector offers significant advantages over other types of detectors. For example, a typical Schottky requires bias for proper operation; a tunnel diode detector has a limited power range because of its negative resistance region; and the point contact diode, because of its fragile construction, is unsuitable for many field applications.

Key Features

- Excellent broadband flatness
- Low broadband SWR
- High burnout protection
- Environmentally rugged

Specifications¹

Specifications describe the product's warranted performance. Supplemental and typical characteristics are intended to provide typical but non-warranted performance parameters. These are denoted as "typical", "nominal" or "approximate".

Model number	33330B	8472B
Frequency range	0.01 to 18 GHz	0.01 to 18 GHz
Frequency response ²		
Octave band flatness	± 0.2 dB over any octave to 8 GHz	± 0.2 dB over any octave to 8 GHz
Broadband flatness	± 0.3 dB to 12.4 GHz ± 0.6 dB to 18 GHz	± 0.3 dB to 12.4 GHz ± 0.5 dB to 15 GHz ± 0.6 dB to 18 GHz
SWR	1.20 ³ to 4 GHz 1.50 ³ to 18 GHz	1.20 to 4.5 GHz 1.35 to 7 GHz 1.50 to 12.4 GHz 1.70 to 18 GHz
Sensitivity	> 0.5 mV/μW	> 0.5 mV/μW
Maximum operating input	200 mW	200 mW
Typical short-term maximum input (less than 1 minute)	1 W	1 W
Noise (μV peak to peak with CW power applied to produce 100 mV output)	< 50 μV	< 50 μV
Output polarity	Negative (default Option 301) Positive (Option 003)	Negative (default Option 301) Positive (Option 003)
Video impedance	1.3 kΩ	1.3 kΩ
RF bypass capacitor	30 pF	50 pF
Input connector	3.5 mm (m)	SMA (m)
Output connector	SMC (m)	BNC (f) (default Option 101) OSSM (f) (Option 100)
Option 001: Matched response ⁴	± 0.2 dB to 12.4 GHz ± 0.3 dB to 18 GHz	± 0.2 dB to 12.4 GHz ± 0.3 dB to 18 GHz

1. Measured at 25 °C and < -20 dBm unless otherwise specified.

2. Below 1 GHz RF may leak through the video connector. If objectionable, this may be eliminated with a low pass filter.

3. Measured at 2 dBm

4. Option 001 must be ordered for each matched pair. Default is Option 101 (33330B)/Option 401 (8472B), no matched pair.

Environmental Specifications

Keysight 33330B/8472B is designed to fully comply with Keysight's product operating environment specifications. The following are the summarized environmental specifications for this product.

Model number	33330B/8472B
Operating temperature	-20 °C to +85 °C
Vibration	20 G, 80 – 2000 Hz
Shock	100 g, 11 ms

Ordering Information

33330B coaxial detector	
Option 101	(default) No matched pair
Option 001	Matched response
Option 301	(default) Negative polarity
Option 003	Positive polarity

8472B coaxial detector	
Option 401	(default) No matched pair
Option 001	Matched response
Option 002	Optimal square law load
Option 301	(default) Negative polarity
Option 003	Positive polarity
Option 101	(default) BNC (f) output connector
Option 100	OSSM (f) output connector

myKeysight

myKeysight

www.keysight.com/find/mykeysight

A personalized view into the information most relevant to you.



www.axistandard.org

AdvancedTCA® Extensions for Instrumentation and Test (AXIe) is an open standard that extends the AdvancedTCA for general purpose and semiconductor test. Keysight is a founding member of the AXIe consortium. ATCA®, AdvancedTCA®, and the ATCA logo are registered US trademarks of the PCI Industrial Computer Manufacturers Group.



www.lxistandard.org

LAN eXtensions for Instruments puts the power of Ethernet and the Web inside your test systems. Keysight is a founding member of the LXI consortium.



www.pxisa.org

PCI eXtensions for Instrumentation (PXI) modular instrumentation delivers a rugged, PC-based high-performance measurement and automation system.



Three-Year Warranty

www.keysight.com/find/ThreeYearWarranty

Keysight's commitment to superior product quality and lower total cost of ownership. The only test and measurement company with three-year warranty standard on all instruments, worldwide.



Keysight Assurance Plans

www.keysight.com/find/AssurancePlans

Up to five years of protection and no budgetary surprises to ensure your instruments are operating to specification so you can rely on accurate measurements.



www.keysight.com/go/quality

Keysight Technologies, Inc.
DEKRA Certified ISO 9001:2008
Quality Management System

Keysight Channel Partners

www.keysight.com/find/channelpartners

Get the best of both worlds: Keysight's measurement expertise and product breadth, combined with channel partner convenience.

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at: www.keysight.com/find/contactus

Americas

Canada	(877) 894 4414
Brazil	55 11 3351 7010
Mexico	001 800 254 2440
United States	(800) 829 4444

Asia Pacific

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 112 929
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Other AP Countries	(65) 6375 8100

Europe & Middle East

Austria	0800 001122
Belgium	0800 58580
Finland	0800 523252
France	0805 980333
Germany	0800 6270999
Ireland	1800 832700
Israel	1 809 343051
Italy	800 599100
Luxembourg	+32 800 58580
Netherlands	0800 0233200
Russia	8800 5009286
Spain	0800 000154
Sweden	0200 882255
Switzerland	0800 805353
	Opt. 1 (DE)
	Opt. 2 (FR)
	Opt. 3 (IT)
United Kingdom	0800 0260637

For other unlisted countries:
www.keysight.com/find/contactus
(BP-06-06-14)

