

LIV Test Systems

	2602A	2612A	System 25	2520
Page	192	192	329	321
Max. Drive Current	3 A DC / 10 A pulsed per channel	1.5 A DC / 10 A pulsed per channel	5 A	5 A
Source Mode	DC (Continuous Wave)	Pulse / DC (Continuous Wave)	DC (Continuous Wave)	Pulse / DC (Continuous Wave)
Number of Channels	1 Laser Drive, 1 Photodiode	1 Laser Drive, 1 Photodiode	1 Laser Drive, 2 Photodiode	1 Laser Drive, 2 Photodiode

Optical Power Measurement

	2502	6487	6485	Photodiode Measurement 2635A/2636A
Page	335	248	245	192

CURRENT MEASURE

From	15 fA	20 fA	20 fA	120 fA
To	20 mA	20 mA	20 mA	10 A

PHOTODIODE VOLTAGE BIAS

	100V (each channel)	500 V	none	200 V
--	------------------------	-------	------	-------

FEATURES

Optical Measurement Head	2500INT Series (Si & Ge) (190nm – 1800nm)	2500INT Series (Si & Ge) (190nm – 1800nm)	2500INT Series (Si & Ge) (190nm – 1800nm)	
Number of Channels	2	1	1	1/2
Instrument Connection	3-slot Triax	3-slot Triax	BNC	3-slot Triax
Communication	GPIB, RS-232	GPIB, RS-232	GPIB, RS-232	GPIB, RS-232, Ethernet (LXI)

Laser Diode and LED Current Drivers

	2601A	2611A	2400-LV	2420	2440	2520	6220 6221
Page	192	192	332, 208	332, 208	332, 208	321	235

CURRENT SOURCE

From	5 pA	5 pA	±50 pA	±500 pA	±500 pA	70 μA	80 fA
To	3 A DC / 10 A pulsed per channel	1.5 A DC / 10 A pulsed per channel	±1 A	±3 A	±5A	+ 5A	±100 mA
Type	DC/Pulse	DC/Pulse	DC	DC	DC	DC/Pulse	DC/Pulse

VOLTAGE MEASURE

From	1 μV	1 μV	10 μV	10 μV	10 μV	60 μV	10 nV (w/2182A)
To	40 V	200 V	20 V	60 V	40 V	10 V	100 V (w/2182A)

FEATURES

Instrument Connection	Screw Terminal	Screw Terminal	Banana	Banana	Banana	10Ω BNC	3-slot Triax
Communication	GPIB/RS-232, TSP, Ethernet (LXI)	GPIB/RS-232, TSP, Ethernet (LXI)	GPIB/RS-232	GPIB/RS-232	GPIB/RS-232	GPIB/RS-232	GPIB/RS-232, Ethernet (6221 only)

1.888.KEITHLEY (U.S. only)

www.keithley.com

KEITHLEY

A GREATER MEASURE OF CONFIDENCE