

Screw Terminal Adapter

DESCRIPTION

The RJ45-STA allows for an easy, reliable and reusable connection to all Micro-Measurements data systems that utilize the RJ45 connector. The RJ45-to-screw-terminal-block adapter has a 6-inch pigtail to allow manipulation and access to the screw terminal block, even when the RJ45 is connected to a data system. The screw terminal block accepts up to 22 AWG wire. Requires a 2 mm slotted screwdriver.



COMPATIBLE WITH:

- System 9000 StrainSmart® Data Acquisition System
- System 8000 StrainSmart® Data Acquisition System
- System 7000 StrainSmart® Data Acquisition System (7003-8-SG, 7003-8-HL, 7003-8-LVDT)
- D4 Data Acquisition Conditioner
- StudentDAQ Student Strain Gage Data Acquisition Device

INSTRUMENTATION COMPARISON

System 9000	System 8000	System 7000	D4	StudentDAQ
<ul style="list-style-type: none"> • Twelve strain gage (strain gauge) input channels • Four configurable plug-in card slots for: <ul style="list-style-type: none"> o High-level voltage signals o Thermocouples o Piezoelectric transducers (charge mode and voltage mode) • Scanning rates of 50,000, 25,000, 10,000 and 5,000 samples/second (all ADCs are sampled simultaneously) • RJ45 input connectors for each strain gage (strain gauge) and high level channel 	<ul style="list-style-type: none"> • Eight software-selectable input channels • Up to 16 scanners can be used concurrently • Supported inputs include: <ul style="list-style-type: none"> o Strain gage (strain gauge) quarter-, half-, and full-bridges o Strain-gage-based transducer o High-level voltage signal o Thermocouples • RJ45 input connectors for each input channel • Scanning rates are 1000, 500, 200, 100, and 10 samples/second 	<ul style="list-style-type: none"> • Individual input cards for strain gage (strain gauge) and strain-gage-based transducers, thermocouples, and sensors with high-level voltage outputs • Virtually unlimited number of channels in increments of 8 channels (contact Applications Engineering for details) • Maximum scan rate of 2048 samples/second 	<ul style="list-style-type: none"> • Four input channels • Hardware and software support for quarter-, half-, and full-bridge circuits • Built-in precision bridge completion • 8-Hz sampling rate • Full control of all functions via USB Interface • Portable, lightweight, and rugged design • Powered via the USB interface 	<ul style="list-style-type: none"> • Single-channel strain gage (strain gauge) data acquisition • Hardware and software support for full-bridge, half-bridge, and quarter-bridge circuits (120 Ω, 350 Ω, 1 kΩ) • Built-in bridge completion • 3-wire strain gage (strain gauge) connection • 80-Hz data rate • Powered via the USB interface

REFERENCES

System 9000 datasheet: <http://www.vishaypg.com/doc?11373>

System 8000 datasheet: <http://www.vishaypg.com/doc?11272>

System 7000 datasheet: <http://www.vishaypg.com/doc?11271>

D4 datasheet: <http://www.vishaypg.com/doc?11257>

StudentDAQ datasheet: <http://www.vishaypg.com/doc?11375>



Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.