

# 1300 WasteWeigh



1300 Indicator



## 1300 Digital Weight Indicator

Our versatile weighing systems are specifically designed for waste and refuse collection vehicles. They provide continuous and precise weight information for payload control and operational efficiency. With the ever-increasing expansion of the waste refuse and recycling industries, we are at the forefront of waste management solutions. The durable WasteWeigh system is designed for high accuracy in rugged environments

## Packer Plate Shutdown

The packer plate shutdown function ensures overloading is prevented by inhibiting the compaction unit when the gross or net alarm point is reached. An override key switch allows the compaction unit to be switched back on by an authorised person.



Packer plate shuts down when maximum load is reached

## AxleWatch

Axle weights are displayed, alerting the driver to any axle overload infringement.

## CCTV

The 1300 combines a weight indicator with a rear-view monitor and features a large, full-colour touch screen with simple-to-use operation.

- Displays net and gross
- Overload alarm
- Easy-to-read LCD display
- Password protection for calibration, load cell swap-outs, and alarm set point
- Print and zero function
- Full-colour touch screen
- Time and date
- AxleWatch
- Packer plate shutdown
- CCTV option



1300 Rear View Monitor



1300 Self Diagnostics



AxleWatch



**We are the UK's largest provider of on-board load control and overload protection systems.**

Airedale House | Canal Road | Bradford BD2 1AG  
 Ph: +44 (0)1274 771177 | Fax: +44 (0)1274 781178  
 E-mail: [obw.eur@vpgsensors.com](mailto:obw.eur@vpgsensors.com)

[vpgonboard.com](http://vpgonboard.com)

**VPG**  
**ONBOARD**  
**WEIGHING**

## Features and Benefits

- High accuracy  $\pm 0.5\%$  FSD or better
- 6.4" colour TFT touch screen
- Speaker for audio output/beep
- CAN 2.0B communication
- Operating voltage 12-32V
- 3 reversing camera inputs (PAL), each with audio
- 12V for cameras regulated in CPU box
- Real-time clock

## Safety

With legislation requiring refuse collection vehicles to have a device fitted that provides visibility at the rear, the 1300 displays full-colour images from up to 3 cameras.

The 1300 combines precision on-board weighing with a mobile CCTV system. Once a camera has been fitted to a vehicle, evidence shows conclusively that there is a dramatic improvement in safety levels.

This not only saves downtime, but also reduces the cost of repairs to the vehicle and, more importantly, saves lives.

| Features                              | Standard | Option |
|---------------------------------------|----------|--------|
| CAN bus                               | ●        |        |
| Gross vehicle weight display          | ●        |        |
| Net payload display                   | ●        |        |
| Full-colour touch screen display      | ●        |        |
| Alarm sounder                         | ●        |        |
| RS232 output                          | ●        |        |
| Password protection                   | ●        |        |
| AxleWatch                             | ●        |        |
| Camera input software x 3             | ●        |        |
| Cameras (up to 3)                     |          | ●      |
| Packer plate shutdown with key switch |          | ●      |
| In-cab printer – light duty           |          | ●      |
| In-cab printer – heavy duty           |          | ●      |
| Custom printer headers                |          | ●      |
| 511 FreeWeigh – handheld unit         |          | ●      |

## Additional Options

In addition to a host of standard features, there are options to upgrade your on-board WasteWeigh system. These include printers to record on-the-spot weights and the 511 FreeWeigh, which gives users weight information away from the cab and Packer Plate Shutdown for greater control of overloads.



Heavy-duty printer



Sounder



511 FreeWeigh



Thermal printer



Camera

**DISCLAIMER:** ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE. Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product. The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein. VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.** Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at [vpgsensors.com](http://vpgsensors.com). No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG. The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications. Product names and markings noted herein may be trademarks of their respective owners.