

FEATURES

- Resistances from 0.10hm to 500MOhms
- Power Rating 0.1 to 0.25Watt
- Resistance Tolerances to ± 0.5%
- TCR's to ± 50 ppm/K
- Thick Film Resistance Element
- Sizes: 0504 / 0603 / 0805 / 1206
- for High Vacuum Applications





TABLE 1-SPECIFICATIONS

(W) ¹	0504 0.10	0603	0805	1206
(W) ¹	0.10			
	0.10	0.10	0.125	0.25
Trimmed	50	75	100	200
Untrimmed	100	150	200	400
ange	Tolerances Available (%) Temperature Coefficients Available (± ppm/K)² (lower TCR upon request)			
Ω	-	10% to 20% 250	5% to 20% 250	5% to 20% 250
Ω	5% to 20% 100 / 250	5% to 20% 100 / 250	2% to 20% 100 / 250	2% to 20% 100 / 250
0Ω	2% to 10% 100	1% to 10% 100	1% to 10% 50 / 100	1% to 10% 50 / 100
М	1% to 10% 50 / 100	1% to 10% 50 / 100	0.5% to 10% 50 / 100	0.5% to 10% 50 / 100
М	1% to 10% 50 / 100	1% to 10% 50 / 100	0.5% to 10% 50 / 100	0.5% to 10% 50 / 100
MC	2% to 20% 100 / 250	1% to 20% 50 / 100	0.5% to 20% 50 / 100	0.5% to 20% 50 / 100
MOO	-	5% to 20% 100 / 250	2% to 20% 100 / 250	2% to 20% 100 / 250
	Untrimmed ange Ω Ω Ω Ω Μ Μ Μ	Untrimmed 100 ange Temperature C Ω - Ω 5% to 20% 100 / 250 Ω 2% to 10% 100 M 1% to 10% 50 / 100 M 2% to 20% 100 / 250 M 2% to 20% 100 / 250	Untrimmed 100 150 ange Tolerances A Temperature Coefficients Available (: Ω - 10% to 20% 250 Ω 5% to 20% 5% to 20% 100 / 250 Ω 2% to 10% 1% to 10% 100 ΩΩ 1% to 10% 1% to 10% 50 / 100 M 1% to 10% 50 / 100 M 1% to 10% 50 / 100 M 1% to 10% 50 / 100 DM 2% to 20% 1% to 20% 50 / 100 OM - 5% to 20% 50 / 100 OM - 5% to 20% 50 / 100	Untrimmed 100 150 200 ange Tolerances Available (%) Temperature Coefficients Available (± ppm/K)² (lower TCR) Ω - 10% to 20% 250 5% to 20% 250 20 5% to 20% 250 2% to 20% 250 2% to 20% 100 / 250 100 / 250 100 / 250 100 / 250 100 / 250 20 2% to 10% 10% 10% to 10% 10% to 10% 50 / 100 50 / 100 50 / 100 M 1% to 10% 50 / 100 50 / 100 50 / 100 M 1% to 10% 50 / 100 50 / 100 50 / 100 M 2% to 20% 100 250 1% to 20% 50 / 100 50 / 100 DM 2% to 20% 50 / 100 50 / 100 50 / 100 0M 5% to 20% 2% to 20% 50 / 100 50 / 100

¹W @ 70 °C / 0W @ 155 °C ²50 PPM : +25 °C to +125 °C

Temperature Range	-55°C to +155°C
Climactic Cetegory	55 / 155 / 56
Solderability	250°C / 3s
Max. Soldering Temperature	260°C / 10s

ORDERING INFORMATION

Part Number - Resistance - Tolerance - TCR - Packaging

CRS 0603 1 Ohm 5% 100ppm Tape

(Note: if no TCR is specified, the highest value will be supplied)



TABLE 1—SPECIFICATIONS (continued)

Long Term Stability	Max ∆R			
Long Term Stability	<10Ω	10Ω - 100M	>100M	
Storage 125°C / 1000h	<1%	<0.5%	<1%	
Storage 155°C / 1000h	<2%	<1%	<2%	
Load Life / P=70% / 70°C / 1000h	<1%	<0.5%	<1%	
Short term overload (rated power x 2.5 for 5s)	<0.5%	<0.25%	<0.5%	
Humidity / 96%RH / 40°C / 56 days	<1%	<0.5%	<1%	

FIGURE 1-DERATING






FIGURE 2-DIMENSIONS in inches [mm]

Type (larger sizes upon request)	Dimensions				
	L	В	D	С	
CRS 0504	0.050 +0.006 / -0.002 [1.25 +0.15 / -0.05]	0.040 +0.006 / -0.002 [1.0 +0.15 / -0.05]	0.012 +0.006 / -0.002 [0.3 +0.15 / -0.05]	0.008 +0.008 / -0.004 [0.2 +0.2 / -0.1]	
CRS 0603	0.060 +0.006 / -0.002 [1.5 +0.15 / -0.05]	0.030 +0.006 / -0.002 [0.8 +0.15 / -0.05]	0.016 +0.006 / -0.002 [0.4 +0.15 / -0.05]	0.008 +0.008 / -0.004 [0.2 +0.2 / -0.1]	
CRS 0805	0.080 +0.006 / -0.002 [2.0 +0.15 / -0.05]	0.050 +0.006 / -0.002 [1.25 +0.15 / -0.05]	0.016 +0.006 / -0.002 [0.4 +0.15 / -0.05]	0.012 +0.008 / -0.004 [0.3 +0.2 / -0.1]	
CRS 1206	0.126 +0.006 / -0.002 [3.2 +0.15 / -0.05]	0.060 +0.008 / -0.002 [1.5 +0.2 / -0.05]	0.016 +0.006 / -0.002 [0.4 +0.15 / -0.05]	0.012 +0.008 / -0.004 [0.3 +0.2 / -0.1]	







Legal Disclaimer Notice

Vishay Precision Group, Inc.

Disclaimer

ALL PRODUCTS. PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.

Document No.: 63999 Revision: 15-Jul-2014